

11-27-00

A

3c871 U.S. PTO

11/25/00

Please type a plus sign (+) inside this box ☒ Approved for use through 10/31/2002. OMB 0651-0032  
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b>  <i>(Only for new nonprovisional applications under 37 CFR 1.53(b))</i>	Attorney Docket No.	NPS018US
	First Inventor	PAUL LAPSTUN
	Title	VIEWER WITH CODE SENSOR AND PRINTER
	Express Mail Label No.	EK285768834US

<b>APPLICATION ELEMENTS</b> <i>See MPEP chapter 600 concerning utility patent application contents.</i>	<b>ADDRESS TO:</b> Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> Fee Transmittal Form (e.g., PTO/SB/17) <i>(Submit an original and a duplicate for fee processing)</i> 2. <input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. 3. <input checked="" type="checkbox"/> Specification [Total Pages <b>32</b> ] <i>(preferred arrangement set forth below)</i> - Descriptive title of the invention - Cross Reference to Related Applications - Statement Regarding Fed sponsored R & D - Reference to sequence listing, a table, or a computer program listing appendix - Background of the invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 4. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets <b>24</b> ] 5. Oath or Declaration [Total Pages <b>3</b> ] a. <input checked="" type="checkbox"/> Newly executed (original or copy) Copy from a prior application (37 CFR 1.63 (d)) (for continuation/divisional with Box 17 completed) b. <input type="checkbox"/> <b>DELETION OF INVENTOR(S)</b> Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). i. <input type="checkbox"/> <b>DELETION OF INVENTOR(S)</b> Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). 6. <input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76	7. <input type="checkbox"/> CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix) 8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Form (CRF) b. Specification Sequence Listing on: i. <input type="checkbox"/> CD-ROM or CD-R (2 copies); or ii. <input type="checkbox"/> paper c. <input type="checkbox"/> Statements verifying identity of above copies
<b>ACCOMPANYING APPLICATION PARTS</b>	
9. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s)) 10. <input type="checkbox"/> 37 CFR 3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney 11. <input type="checkbox"/> English Translation Document (if applicable) 12. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations 13. <input type="checkbox"/> Preliminary Amendment 14. <input type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 15. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. <input type="checkbox"/> Other:	

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Prior application information. Examiner: \_\_\_\_\_ Group / Art Unit: \_\_\_\_\_

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

**18. CORRESPONDENCE ADDRESS**

☒ Customer Number or Bar Code Label **24011** or ☐ Correspondence address below  
*(Insert Customer No. or Attach bar code label here)*

Name	KIA SILVERBROOK				
Address	393 Darling Street,				
City	Balmain	State	NSW	Zip Code	2041
Country	Australia	Telephone	+61-2-9818-6633	Fax	+61-2-9819-6711

Name (Print/Type)	KIA SILVERBROOK	Registration No. (Attorney/Agent)	
Signature	<i>[Signature]</i>	Date	November 22, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

**FEE TRANSMITTAL  
for FY 2001**

Patent fees are subject to annual revision

**Complete if Known**

Application Number	
Filing Date	
First Named Inventor	PAUL LAPSTUN
Examiner Name	
Group Art Unit	
Attorney Docket No	NPS018US

TOTAL AMOUNT OF PAYMENT (\$ 475)

**METHOD OF PAYMENT**

- 1.
- ☐
- The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to.

Deposit Account Number

Deposit Account Name

☐ Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17☐ Applicant claims small entity status See 37 CFR 1.27

- 2.
- ☒
- Payment Enclosed:

☒ Check ☐ Credit card ☐ Money Order ☐ Other**FEE CALCULATION****1. BASIC FILING FEE**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
101 710	201 355	Utility filing fee	355
106 320	206 160	Design filing fee	
107 490	207 245	Plant filing fee	
108 710	208 355	Reissue filing fee	
114 150	214 75	Provisional filing fee	

SUBTOTAL (1) (\$ 355)

**2. EXTRA CLAIM FEES**

Total Claims  -20\*\* =  X  =

Independent Claims  -3\*\* =  X  =

Multiple Dependent  =

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
103 18	203 9	Claims in excess of 20
102 80	202 40	Independent claims in excess of 3
104 270	204 135	Multiple dependent claim, if not paid
109 80	209 40	** Reissue independent claims over original patent
110 18	210 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$ 0)

\*\*or number previously paid, if greater, For Reissues, see above

**FEE CALCULATION (continued)****3. ADDITIONAL FEES**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
105 130	205 65	Surcharge - late filing fee or oath	
127 50	227 25	Surcharge - late provisional filing fee or cover sheet	
139 130	139 130	Non-English specification	
147 2,520	147 2,520	For filing a request for ex parte reexamination	
112 920*	112 920*	Requesting publication of SIR prior to Examiner action	
113 1,840*	113 1,840*	Requesting publication of SIR after Examiner action	
115 110	215 55	Extension for reply within first month	
116 390	216 195	Extension for reply within second month	
117 890	217 445	Extension for reply within third month	
118 1,390	218 695	Extension for reply within fourth month	
128 1,890	228 945	Extension for reply within fifth month	
119 310	219 155	Notice of Appeal	
120 310	220 155	Filing a brief in support of an appeal	
121 270	221 135	Request for oral hearing	
138 1,510	138 1,510	Petition to institute a public use proceeding	
140 110	240 55	Petition to revive - unavoidable	
141 1,240	241 620	Petition to revive - unintentional	
142 1,240	242 620	Utility issue fee (or reissue)	
143 440	243 220	Design issue fee	
144 600	244 300	Plant issue fee	
122 130	122 130	Petitions to the Commissioner	
123 50	123 50	Petitions related to provisional applications	
126 240	126 240	Submission of Information Disclosure Stmt	
581 40	581 40	Recording each patent assignment per property (times number of properties)	120
146 710	246 355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149 710	249 355	For each additional invention to be examined (37 CFR § 1.129(b))	
179 710	279 355	Request for Continued Examination (RCE)	
169 900	169 900	Request for expedited examination of a design application	

Other fee (specify) \_\_\_\_\_

\* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$ 120)

**SUBMITTED BY**Name (Print/Type) **Kia Silverbrook**

Registration No. (Attorney/Agent)

**Complete (if applicable)**Telephone **+61-2-9818-6633**Signature Date **Nov. 22, 2000****WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.**

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

## VIEWER WITH CODE SENSOR AND PRINTER

### FIELD OF INVENTION

- The present invention relates generally to devices for interacting with computer systems, and in particular, to a device which may be used to render otherwise passive surfaces audiovisually interactive via invisible surface codings.

### CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present invention:

- 10 NPA060US, NPA061US, NPA081US, NPA082US, NPP010US, NPP013US, NPP015US, NPP020US, NPP021US, NPP022US, NPP023US, NPS014US, NPS015US, NPS017US, NPS018US, NPS022US, NPS027US, NPS028US, NPT008US, BIN01US, BIN02US, BIN03US, BIN04US

- 15 The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of

- 20 the present invention on 20 October 2000:

NPA011US, NPA031US, NPA040US, NPA046US, NPA053US, NPA059US, NPA064US, NPB006US, NPS004US, NPS008US, NPS013US, NPS024US, NPPC1, UP01US, UP02US, UP03US, UP04US, UP05US

- 25 The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of

- 30 the present invention on 15 September 2000:

NPA024US, NPA025US, NPA047US, NPA049US

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

Various methods, systems and apparatus relating to the present invention are  
5 disclosed in the following co-pending applications filed by the applicant or assignee of the present invention on 30 June 2000:

10 NPA014US, NPA015US, NPA022US, NPA026US, NPA038US, NPA041US,  
NPA050US, NPA051US, NPA052US, NPA063US, NPA065US, NPA067US,  
NPA068US, NPA069US, NPA071US, NPA072US, NPB003US, NPB004US,  
NPB005US, NPP019US, PEC04US, PEC05US, PEC06US, PEC07US

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

15 Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention on 23 May 2000:

20 NPA001US, NPA002US, NPA004US, NPA005US, NPA006US, NPA007US,  
NPA008US, NPA009US, NPA010US, NPA012US, NPA016US, NPA017US,  
NPA018US, NPA019US, NPA020US, NPA021US, NPA030US, NPA035US,  
NPA048US, NPA075US, NPB001US, NPB002US, NPK002US, NPK003US,  
NPK004US, NPK005US, NPM001US, NPM002US, NPM003US, NPM004US,  
NPN001US, NPP001US, NPP003US, NPP005US, NPP006US, NPP007US,  
NPP008US, NPP016US, NPP017US, NPP018US, NPS001US, NPS003US,  
25 NPS020US, NPT001US, NPT002US, NPT003US, NPT004US, NPX001US,  
NPX003US, NPX008US, NPX011US, NPX014US, NPX016US, IJ52US,  
IJM52US, MJ10US, MJ11US, MJ12US, MJ13US, MJ14US,  
MJ15US, MJ34US, MJ47US, MJ58US, MJ62US, MJ63US,  
PAK04US, PAK05US, PAK06US, PAK07US, PAK08US, PEC01US,  
30 PEC02US, PEC03US

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

35

## BACKGROUND

Devices such as personal computers, personal digital assistants and even mobile phones may be used to interact with audiovisual information and with computer applications which have an audiovisual interface.

- 5           In general, these devices don't provide access to situated interactive information or application interfaces, e.g. to an online fan club chat group associated with a concert poster encountered at a train station, or a mortgage calculator associated with a flyer received through the mail. Each device must be used to seek out the desired information or application interface through a virtual space accessible through the
- 10          device, or the information or application must be brought to the device in a device-compatible physical format.

- The present invention utilizes methods, systems and devices related to a system referred to as "netpage", described in our co-pending applications listed above, wherein invisible coded data is disposed on various surfaces to render the surfaces interactive in
- 15          the manner of graphical user interfaces to computer systems.

## SUMMARY OF INVENTION

- In one broad form the invention provides a viewer with one or more sensors capable of sensing coded data. Images which include coded data are sensed by the viewer and decoded. The decoded information is transmitted to a computer system which
- 20          associates the decoded data with one or more files stored on the system, using previously stored association data. The file or files are transmitted to the viewer and to the user via the viewer's display screen. The device includes a printing mechanism which allows markings to be made on a substrate. The markings may be based partially or wholly on user input or on data transmitted from the computer system to the viewer.

- 25          Accordingly, in one broad form, the invention provides a viewer including:

            at least one sensor for sensing coded data on or in a substrate and for generating first data;

- a transceiver for transmitting said first data or second data at least partially based on the first data to a computer system and for receiving at least display data
- 30          associated with an identity derived from the first data from the computer system;

at least one display device for outputting visual information based at least partially on said display data, and

a printer mechanism for printing on the substrate.

Printer mechanisms other than conventional ink deposition type print mechanisms may be used. Examples of other types of print mechanisms include the use of thermal paper, such as used in facsimile machines. In addition the substrate may be imprinted with electronically active inks and the print mechanism may be a device for selectively changing the state of the electronically active inks. For a better understanding of electronically active inks, reference is made to US Patent Nos. 6017584, 6124851, 6120839, 6,120,588, 6,118,426 and 6,067,185, all assigned to E Ink Corporation, the contents of each of which are included herein by reference.

In one form the visual output corresponds to a human discernable interface on the substrate, such as text.

In use the viewer may be moved across a substrate tiled with data encoded tags and the output is modified as the viewer is moved across the substrate so as to correspond to the interface on the substrate.

The optical output may correspond to the interface but be text in the same or a different language as the interface. The optical output may include the same, more or less information as the interface on the substrate. The interface may represent information, such as bank account information which is not displayed on the interface in full but is displayed in full via the viewer.

The device preferably has controls to enable the optical output to display information with a size the same, less or more than the corresponding information on the interface.

The device preferably includes a touch screen and the optical output includes interactive elements by which the user may modify the optical output by interaction with the touch screen.

The touch screen may be used to input writing or other markings from the user. The viewer may then print markings on the substrate based on the user input markings. The markings printed may be substantially identical to the user input markings or may be

printed text corresponding to user input handwriting after the user input has undergone text recognition processes.

The device may also display motion pictures, in which case the physical relationship between the viewer and the substrate once the coded data has been transmitted may be immaterial.

The viewer may also include memory into which a file or files are downloaded for subsequent viewing.

When the viewer is lifted from the page the portion of the page with which the viewer was last in contact can be retained by the viewer and remain interactive. The viewer can do this by default, or alternatively only when the user 'freezes' or 'snaps' the current view before lifting the viewer from the page, as discussed in more detail below. The viewer may include controls for rotating and panning the view after the viewer has been lifted from the page, allowing the viewer to be used to navigate an entire page after only a single contact with it. The navigation controls may be in the form of a small joystick, or a pair of orthogonal thumb wheels, or may be provided via the touch-screen.

The viewer senses the identity of the underlying page as well as its own position and orientation relative to the page using a netpage sensor embedded in the viewer. The viewer can contain multiple sensors (one in each corner, for example), so that it works when only partially overlapping a page or even when overlapping multiple pages. A single sensor located in the center of the viewer is sufficient for most purposes, however, and is most economical.

The viewer is capable of providing an enhanced view of the underlying page. In the dark, for example, it can provide a lit view of the page. When magnification is needed, it can provide a zoomed view of the page via its zoom controls. The viewer may also be able to provide a zoomed-out view of the page.

The viewer can provide an alternative (or additional) netpage data entry mechanism, i.e. the usual kinds of inputs, including drawing and handwriting and gestures, can be captured relative to the displayed page via the touch-screen instead of relative to the physical page via the netpage pen.

The viewer can provide access to dynamic content, such as audio and video, in the context of a physical page. Playback controls which provide access to interactive content are typically only shown when the page is viewed through the viewer. They may be shown on the printed page as well, although ideally in a form which clearly indicates that they are inactive. Status information such as playing time may also be shown on-screen. The underlying page layout should provide space for the display of interactive controls and status information, so that the printed page and on-screen display remain compatible. Interactive control is not limited to playback of streaming media such as audio and video. It can include arbitrary interaction with a computer application. It may, for example, include manipulation of an object in 3D.



## **BRIEF DESCRIPTION OF DRAWINGS**

Figure 1 is a perspective view from above of an embodiment of the invention;

Figure 2 is a perspective view from below of the Figure 1 device;

Figure 3 is an exploded perspective view from above of the Figure 1 device;

5 Figure 4 is a side view from the rear of the device of Figure 1;

Figure 5 is a plan view from above of the Figure 1 device;

Figure 6 is a side view from the right of the Figure 1 device;

Figure 7 is a cross-sectional view taken along line AA of Figure 5;

10 Figure 8 is a perspective view from above of the internal components of the Figure 1 device;

Figure 9 is a perspective view from below of the internal components of the Figure 1 device;

Figure 10 is an exploded perspective view of the underside of the PCB of the Figure 1 device;

15 Figure 11 is a plan view showing the Figure 1 device in use on a coded substrate in a first orientation;

Figure 12 is a view from the side of the Figure 11 arrangement;

Figure 13 is a plan view of the Figure 1 device in a second orientation on the substrate of Figure 11.

20 Figure 14 is a plan view of the Figure 1 device viewer showing a 'lifted' view of a page;

Figure 15 is a plan view of the Figure 1 device showing a view of a page in darkness;

Figure 16 is a plan view of the Figure 1 device showing a 'zoomed-in' view of a page;

Figure 17 is a plan view of the Figure 1 device showing a 'zoomed-out' view of a page;

Figure 18 is an example of a movie library page;

25 Figure 19 is a plan view of a viewer showing a view of a playable video clip;

Figure 20 is a plan view of a viewer showing a snapped and lifted view of a playable video clip;

Figure 21 shows an example of a music library page;

Figure 22 shows a plan view of a viewer showing a view of playable music clip;

- 5 Figure 23 shows a plan view of a viewer showing a snapped and lifted view of a playing audio clip;

Figure 24 shows an example of PIN advice letter from bank;

Figure 25 shows a viewer showing a secure view of personal data;

Figure 26 shows an example of "fill-in" form;

- 10 Figure 27 shows a viewer allowing form fill-in by a user;

Figure 28 shows the "fill-in" form of figs 26 & 27 after printing on by the viewer;

Figure 29 shows a schematic of part of the viewer's electronic components, relating to file download and display;

Figure 30 shows a schematic of part of the viewer's electronic components relating to

- 15 control of the printer functions;

Figure 31 shows a document element view; and

Figure 32 shows the viewer interaction with a netpage network.

## DETAILED DESCRIPTION OF PREFERRED AND OTHER EMBODIMENTS

Referring to Figs. 1 to 10, there is shown a viewer 100. The viewer has a color LCD screen 102, control buttons 186, 192 & 194, a speaker 106, volume control 108, an audio out jack 110, a printer assembly 200 and an infrared sensing device 112. The LCD screen 102 has a touch sensitive overlay 132.

The viewer 100 is a netpage system enabled device and communicates with a netpage system in a similar manner to that disclosed in the co-pending applications referred to earlier and in particular to applications USSN 09/\_\_\_\_\_ (docket no. NPP023US) and USSN 09/\_\_\_\_\_ (docket no. NPS027US).

10 The viewer 100 has upper and lower moldings 114 and 116 respectively which encapsulate a PCB 118 and all of the electronic components are mounted on or connected to this PCB. Power for the device is supplied by a rechargeable 3 volt lithium ion battery 120. The battery is not user replaceable and is located within the casing.

15 The PCB 118 and attached electronics is attached to the upper molding 114 by screws 125. The printer assembly 200 is attached to the lower molding 116 by screws 240, which pass through the chassis 224 into bosses 242 in the lower molding 116.

The two moldings 114 and 116 are joined together by four screws 124, which extend through the lower molding 116 to engage the upper molding 114.

20 The PCB includes four electrical switches which are acted on by the push buttons. The zoom buttons 186 allows the view to be zoomed in, zoomed out, and, when activated simultaneously, to be reset to normal scale. The snap button allows the nearest dynamic or interactive object to be snapped to the screen. It more generally allows the current view to be de-synchronized (or 'frozen' or 'lifted') from the underlying page. Optional pan controls allow the view to be panned independently of the underlying page.

25 The power button allows the viewer to be switched on and off. The volume control, in the form of a potentiometer, allows the volume of the viewer's audio output to be controlled. The audio output is used to play audio content associated with a page, and optionally to provide operating feedback to the user.

30 A combined data and power connector 134 is connected to the PCB and is accessible via opening 136 in the casing. The connector 134 includes a power input

socket 138 for recharging of the battery 120 and a data socket 140 for input/output of data to and from the device. The connector 134 is connected to the PCB via a flexible PCB 142 and connectors 144 and 146.

5 The speaker 106 is also connected to the PCB at its lower edge via connector 148 and is positioned between the PCB and the lower edge of the casing. The speaker may be hard wired to the PCB rather than being provided with a removable connector.

Digital audio generated by the viewer is converted to analog via a digital-to-analog converter (DAC) 173, is amplified by an amplifier 177 subject to the volume control 108, and is output to a speaker 106 or to an external audio device via an audio  
10 out jack 110. The speaker is disabled when the audio jack is in use.

The volume control 108 and audio out jack 110 are mounted directly on the left hand side of the PCB and are accessible via openings 154 and 156 respectively in the left hand side of the casing.

15 The battery 120 is also positioned between the PCB and the lower edge of the casing. A removable connector 150 is provided to connect the battery to the PCB. However, since the battery is not intended to be user replaceable, a permanent connection may be used. The battery is preferably shaped to fit the casing and accordingly has a beveled corner 152.

20 Mounted on the lower surface of the PCB is the optical sensor device 112 capable of detecting infrared markings on a substrate. The sensing device 112 comprises an infrared LED 160 and an image sensor 162. In use infrared light is emitted from the LED 160 and passed through an optical guide 164 and then through an aperture 166 in the lower molding. Reflected light passes through the aperture 166, the optical molding 164 and is focused onto the CCD 162. The optical molding preferably includes a lens  
25 168 and may include a beam splitter/combiner to allow light from and to the LED and the CCD to follow the same path. The LED 160 may be strobed in synchrony with image capture to prevent motion-blurring of captured tag images. The image sensor 162 typically consists of a 200x200 pixel CCD or CMOS image sensor with a near-infrared bandpass filter.

The PCB also includes a processor chip 170, DRAM 172, flash ROM 174, a display controller 270 for controlling the LCD, a transceiver chip 178 and an aerial 180.

In order to display video, the color display 102 usefully has a 4:3 aspect ratio, although with the advent of DVD and digital broadcasting, digital video content with  
5 wide screen aspect ratios of 16:9 and wider are becoming more prevalent. The aspect ratio used is not critical. The minimum useful resolution is preferably SIF resolution, which has a square-pixel equivalent of 320x240 pixels. In order to display text, the display preferably has a pitch of at least 100 pixels per inch, giving a maximum diagonal display size of four inches. Larger displays with correspondingly more pixels provide  
10 obvious benefits, although with the added expense of a larger form factor and greater processing and communications bandwidth requirements.

The display ideally mimics the optical properties of the underlying paper, i.e. the paper's high reflectivity, high contrast, and Lambertian reflectance function. Although the display may be a conventional back-lit color LCD, such as an active-matrix  
15 twisted-nematic (TN) color LCD, it is more usefully a reflective display, such as a passive-matrix cholesteric color LCD from Kent Displays Inc, an electrophoretic display from E Ink Corporation, or a rotating ball display from Xerox Corporation, Inc. It may also be a low cost organic LED (OLED) display.

Display output generated by the viewer is routed to the display 102 via the  
20 display controller 270. Assuming a 320x240 RGB pixel display, the display controller 270 has an associated or embedded 0.25 Mbyte single-buffered or 0.5 Mbyte double-buffered display memory 181.

A dedicated compressed video and audio decoder 171 which produces square-pixel progressive-scan digital video and digital audio output is also provided. To handle  
25 MPEG-1 encoded video and audio, a video and audio decoder similar to a C-Cube CL680 decoder may be used. To handle MPEG-2 encoded video and audio, a video and audio decoder similar to C-Cube's ZiVA-3 decoder may be used. An MPEG-1 decoder typically uses a 4 Mbit DRAM during decoding, while an MPEG-2 decoder typically uses a 16 Mbit SRAM during decoding. The decoder memory 179 may be dedicated to  
30 the decoder, or may be part of a memory 172 shared with the processor.

The processor 175 controls and coordinates the various electronic components of the viewer. The processor executes software which monitors, via the sensor(s) 112, the identity of the underlying page and the position of the viewer relative to the page; communicates the identity and position data to a netpage base station via the wireless transceiver 183,178; receives identity- and position-related page data from the base station via the transceiver; renders user output to the color display 102 and audio output; and interprets user input captured via the user interface buttons 104 and the screen's touch sensor 132. The embedded software executed by the processor is stored in the non-volatile memory 174, which is typically a ROM and/or flash memory. Identity information unique to the viewer, as well as communications encryption keys, are also stored in non-volatile memory. During execution the processor utilizes faster volatile memory, typically in the form of a 256 Mbit (32 Mbyte) dynamic RAM (DRAM) 172.

The processor 175 communicates with the other components via a shared bus 280. The processor 175, the bus 280, and any number of other components may be integrated into a single chip. As indicated in Fig. 28 the integrated components may include the digital transceiver controller 183, the video decoder interface 187 and the tag image sensor interface 185. If a fingerprint sensor 189 is provided a fingerprint sensor interface 191 may be incorporated in the integrated components. In a more highly integrated chip, the integrated components may also include the display controller 270, the image sensor 112, the compressed video and audio decoder 171, the audio digital-to-analog converter (DAC) 173 and the memory 172. The analog radio transceiver 178 is unlikely to be integrated in the same chip, but may be integrated in the same package. A parallel interface 193 links the buttons 104, touch sensor 132 and the LED 160 to the bus 280.

The processor 175 is sufficiently powerful to render page content at interactive rates, i.e. at least 10 Hz, and to transform video decompressed by the video decoder and merge it with other page content. If it is sufficiently powerful, then it may also perform video and audio decoding, obviating the need for a video and audio decoder.

The transceiver 178 is typically a short-range radio transceiver. It may support any of a number of wireless transmission standards, including Bluetooth/IEEE 802.15, IEEE 802.11, HomeRF/SWAP, HIPERLAN, and OpenAir. Bluetooth/IEEE 802.15,

IEEE 802.11-1997, HIPERLAN, OpenAir, and HomeRF/SWAP all support transmission rates in the range of 1 to 2 Mbit/s. IEEE 802.11b supports transmission rates of 5.5 Mbit/s and 11Mbit/s. HIPERLAN also supports a transmission rate of 24Mbit/s in an alternative mode. Beyond these currently-supported wireless LAN (WLAN) standards, 5 next-generation WLAN standards promise to support transmission rates of 100 Mbit/s and higher.

The viewer may alternatively be connected to the a base station by cable, or may utilize a non-radio-frequency wireless transport, such as infrared. IEEE 802.11, for example, optionally utilizes an infrared transport. IrDA also utilizes an infrared 10 transport.

The lower surface of the lower casing 16 is provided with four outer feet 182 and four inner feet 184. The outer feet are located near the corners of the device whilst the inner feet 184 are located at the corners of a square centered on the lens 168.

All eight feet extend the same distance and enable the device to be placed on a 15 planar surface with a small gap between the surface and the general plane of the lower molding. The feet have a rounded contact surface and this aids in sliding the device across the surface. The inner feet 184 ensure that if one or more of the outer feet 182 are not supported the device does not tip relative to the surface. They also aid in keeping the surface flat near the sensing device 112.

20 The sensor device 112 is infrared sensitive. The CCD 162 is sensitive to infrared light, either inherently or by use of filters and the LED 160 emits infrared light, again inherently or by use of filters. The lens 168 is focused on the plane of the inner and outer feet 182 and 184, as this is where a substrate to be sensed will be located. The sensor device is capable of detecting infrared absorptive tags, such as netpage tags. For a 25 full description of the processes involved, reference is made to our co-pending application USSN 09/\_\_\_\_\_ (docket no. NPS027US) referred to earlier. The CCD 162, the LED 160 and processing functions incorporated in the processor chip 170 are similar to those disclosed in the co-pending application.

The device is thus capable of sensing and decoding netpage tags on a substrate. 30 Image data captured by the CCD 162 is sent to the processor chip 170 and decoded to a region ID (or page ID) and a tag ID. The region ID and tag ID, together with other

necessary information, is transmitted to the netpage system via the transceiver chip 183,178. The netpage system resolves the region ID and tag ID to corresponding document data which it transmits back to the device. The processor receives the document data via the transceiver, and renders the data for display on the color display  
5 102 via the display controller 270.

The LCD screen 102 is overlaid with a touch sensitive overlay 132. When viewing information via the LCD screen, the screen will include controls to enable the user to control the device by touching the screen with a non-marking stylus.

The viewer 100 also includes a printer assembly, generally indicated by 200,  
10 which is located in the body of the viewer.

The print assembly 200 includes a printhead assembly 202 and an ink cartridge 204 connected together by a hose assembly 206. The printhead assembly 202 includes a printhead 203. The lower molding 116 has an ink cartridge compartment 208 to enable user replacement of the ink cartridge 204. The compartment 208 is accessed via cover  
15 210. The hose assembly 206 includes a connector 212 for connecting to the ink cartridge.

The print assembly 200 is preferably an inkjet type printer and more preferably a full-color inkjet. Accordingly the ink cartridge 204 includes multiple inks. In the preferred embodiment the print assembly is a full-color CMY or CMYK printer and the  
20 ink cartridge 204 includes three or four separate ink chambers 252. Whilst any inkjet printhead may be used, more preferably the printhead is a microelectromechanical system (MEMS) type printhead (Memjet), such as that disclosed in our co-pending application USSN 09/575,141 (docket no. IJ52US).

A Memjet printhead provides a combination of printhead width, compactness,  
25 low power consumption, and low cost which makes it uniquely suitably for integration in the printing viewer. Although a Memjet printhead provides 1600 dpi resolution, a printing viewer may get by with less. If the printing viewer is sufficiently small, then an area printhead can be used rather than a scanning printhead.

The printhead assembly 202 extends across at least the full width of the LCD  
30 screen 102 and prints by moving upwards or downwards. The printhead assembly 202 is



mounted on a continuous elastomeric belt 214 which runs around rollers 216 and 218 located at the top and bottom of the screen. The lower roller 216 is driven by a DC stepper motor 286 via a worm gear 222. The two rollers are mounted on a printer chassis 224. Mounted on each side of the chassis 224 are transverse rods 226. The  
5 printhead assembly 202 is mounted on these rods 226 and these rods maintain the printhead in the correct position; the belt 214 merely causes the printhead assembly 202 to move backwards and forwards along the rods 226.

The lower molding 116 is provided with a rectangular aperture 250 and a metal base plate 236 is attached to the underside of the molding 116. The base plate 236 has a  
10 rectangular aperture 252 sized so that the printhead assembly 202 is not exposed when at either extreme of its travel. The base plate is preferably attached to the lower molding 116 by an adhesive.

The operation of the print assembly 202 is controlled by a dedicated print engine/controller (PEC) chip 281 located on the PCB 118. An example of a suitable PEC  
15 is described in our co-pending application USSN 09/575,108 (docket no. PEC01US). The PEC chip 281 generates bi-level dot data for the printhead in real time and otherwise controls the operation of the printhead. Communication with the printhead assembly 202 is via a flexible PCB 228 which engages the PCB 118 via connector 230. The DC motor 286 is connected to the PCB via a flexible PCB 231.

20 A master QA chip 282 , for example as described in our co-pending application USSN 09/113,223 (docket no. Auth06), is provided which the PEC uses to authenticate an identical QA chip 283 embedded in the replaceable color ink cartridge 204. A raster image processor (RIP) DSP 284 may be used for rendering print data at high speed. Depending on the desired print quality and speed and the performance of the processor,  
25 the RIP DSP may be omitted with the processor performing rasterization. Depending on the need to accurately control ink quality and to monitor consumption, and on the availability of alternate mechanisms for detecting ink depletion, the inclusion of the QA chips may not be needed.

Referring to figure 29, the processor 175 typically communicates with PEC 281  
30 via a serial bus 285. The serial bus 285 may be high-speed or low-speed depending on the desired print quality and speed. The processor 175 controls the stepper motor 286

which moves the printhead assembly 202 via the parallel interface 193.

5 The elastomeric belt 214 and the printhead assembly 202 extend across the full width of the screen 102 and by necessity obscure the sensor 112 as the printhead assembly moves between the rollers 216 and 218. The belt 214 is provided with two pairs of circular apertures 232 and 234. The first pair 232 align when the printhead assembly 202 is adjacent the drive roller 216. The second pair 234 align when the printhead assembly 202 is adjacent the drive roller 218. When the apertures align the sensor 112 may sense coded data on a substrate below the viewer. When the apertures 232 and 234 do not align the sensor 112 cannot sense any data on the substrate.

10 The viewer may be designed so that the code sensor has a view of the surface during printing. The code sensor itself can then be used to detect movement. Movement detected in this way can be used to terminate printing. It can also be used to modify the print data in real time so that the print data is properly registered with the underlying page at all times. Multiple code sensors may be used if located around the periphery of  
15 the viewer.

An accelerometer may be included in the viewer to detect movement of the viewer during printing. If movement is detected, then printing can be immediately terminated.

## USAGE

20 Referring to figures 11 and 12, in use the device 100 is placed on a substrate 200 having netpage tags 202 tiled over its surface. The substrate 200 may be paper, electronic paper such as used by E Ink Corporation, a plastic sheet or any other suitable substrate. As seen in Figure 12 the sensor device 112 senses one or more of the tags 202, decodes the coded information and transmits this decoded information to the netpage  
25 system. In figure 11 the substrate carries human readable text 204 and so is readable without the device 100.

The device may be used with a surface which only carries netpage tags and so appears as a blank document to a user without an authorized viewer. As discussed in our earlier applications, each tag incorporates data which identifies the page it is on and its  
30 location within the page. The netpage system is thus capable of determining the location

of the viewer 100 and so can extract information corresponding to that position. When displaying static images or text the displayed information usually corresponds to the human discernable text or other markings 204 on the substrate. Additionally the tags include information which enables the device and/or system to derive an orientation of the device relative to the page from the tags. This enables the information displayed to be rotated relative to the device to match the orientation of the text 204. Thus information 206 displayed by the viewer appears to be what is on the page in the corresponding position under the viewer.

When the viewer first comes into contact with a new page, it downloads the corresponding page description from the relevant page server. It then renders the viewer's view according to the current view transform, i.e. according to the viewer's current zoom setting and its position and rotation relative to the underlying page. Whenever the view transform changes, i.e. because the user moves the viewer or changes the viewer's zoom setting, the viewer re-renders the view according to the new view transform. For the purposes of the following discussion, the size of the viewer's window onto the page is also assumed to be part of the view transform.

Whenever the view transform changes, the viewer transmits the view transform to the netpage page server responsible for the underlying page. This allows the page server to commence streaming dynamic objects which have come into view and to cease streaming dynamic objects which are no longer in view. It also allows the page server to provide the viewer with static objects, such as images, at a suitable resolution.

As the device is moved the sensor device 112 images the same or different tags, which enables the device 100 and/or system to update the device's relative position on the page and to scroll the LCD display as the device moves. The position of the viewer relative to the page can easily be determined from the image of a single tag; as the viewer moves the image of the tag changes and from this change in image the position relative to the tag can be determined. The system "knows" the absolute position of the tag on the page from its tag ID and so the absolute position of the viewer on the page may be derived. The viewer senses tags, and thereby its time-varying position relative to the substrate, and sufficiently frequently that movement of the viewer results in a smooth, as opposed to a jerky, scrolling of the display.

The information 206 displayed in the viewer is preferably aligned with the text 204 on the page 200, so that it appears as if the viewer 100 is transparent. Thus the orientation of the viewer 100 does not alter the orientation of the displayed information 206, as seen in Fig. 13.

5           However, as seen in Fig. 14, the text 206 displayed on the LCD screen 102 need not remain aligned with the physical text but may remain aligned with the viewer 100. The user may use the 'snap' button 192 to instruct the viewer to display text aligned with the viewer, not the page text 204.

10           The viewer 100, if provided with backlighting of the LCD 132, is capable of displaying information in the dark. Fig. 15 shows a page 200 with a viewer 100 displaying information 206 corresponding to information on the page which is not visible due to lack of ambient light.

15           Whilst the information 206 shown on the LCD 102 is similar to the printed information 204, it need not be identical. The left hand control button 186 is a rocker type device. When pressed on the left, the button activates switch 188 and when pushed on the right the button activates switch 190. Pushing down centrally or equally on the left and right activates both switches 188 and 190. Pressing on the left switch 186 causes the display to zoom in whilst pressing on the right causes the display to zoom out. Pressing centrally resets the display to the device default, which may be a 1 to 1 ratio. Fig. 16  
20           shows a viewer 100 displaying "zoomed-in" text 206 whilst Fig. 17 shows "zoomed-out" text 206, both being of text 204 on a page 200.

25           The device is not limited to simply reproducing the text printed on a page. Because the printed text is associated with one or more electronic documents in the netpage system, the device can provide more than just the text to the user. Where a document has references, such as footnotes or hyperlinks, these references may be shown on screen. The user may then view those references by touching the reference on screen. This is picked up by the touch screen overlay 132 and the appropriate information displayed, either in a new window or as an overlay on the existing text. This information may be displayed for a set period, after which the display reverts to its original display.  
30           The system may also cause additional information to be shown on the LCD screen automatically. Where the page is mainly text the device 100 may be set to a read mode

whereby as the user reads the page the text is recited and output via speaker 106. This would be of benefit to people learning to read, such as children or those learning a foreign language. Using a stylus and the touch screen the user indicates where they are reading and the corresponding text is spoken by the machine. Pronunciation of a word or  
5 phrase may be practiced by repeatedly drawing the stylus over the relevant text.

The text displayed need not be the same language as the text on the paper. The device may be set to display a single language, when possible. Thus if a netpage document exists in both English and Italian, for example, the device could be set to display the Italian text even though the printed document is in English. Where a  
10 document only exists in one language, the system may be configured to either display the document in that language or nothing except a message to the effect that document is not available in the desired language.

If desired the device may be set to an "automatic recital" mode in which the screen automatically scrolls through the entire document, with or without a  
15 corresponding aural recital. An aural recital may also occur without a corresponding display of text. The speed of playback may be controlled by the user. Since each tag 202 on the page identifies the document the device merely needs to sense one tag on the page for those features to be activated.

Depending on the document size and device memory, an entire document may  
20 be downloaded to the device or "chunks" of data may be downloaded as required or as expected to be required. A simple text document, even of many pages, is relatively small and may be buffered in its entirety without needing extra memory; the device is capable of playing video, as will be discussed later, and the buffer needed to accommodate variations in data reception for video display is more than sufficient to accommodate  
25 most text documents. Where an entire document is downloaded, preferably the download is configured to initially send data corresponding to the location of the viewer on the page.

When viewing text or static images the device may have two modes. The first mode, described above, maintains a correlation between the information displayed on the  
30 LCD screen and the position of the device to the substrate. In the second mode, the device may be moved without affecting the display; the scrolling and autoplay feature

discussed above being a subject of this feature. To set the device to the second mode the user may press the 'snap' button 192. Once in the second mode movement of the device across the paper does not automatically affect the information displayed. The information displayed continues to correspond to the location when the viewer was placed in this mode. Movement of information across the display in this mode is controlled by the user. A document will continue to be displayed or be accessible until the device is placed on a different netpage encoded substrate, at which point the device may normally revert to its first mode. Alternatively, the user must explicitly revert to the first mode by pressing the 'snap' button again.

Figs. 18, 19 and 20 provide an example of the interaction of the viewer with a video clip. Fig. 18 shows a sample 'movie library' page 210 containing multiple video clip icons 212. Again the page is tiled with netpage tags, not shown. Fig. 19 shows the view the viewer provides of a video clip icon, which includes playback controls 214, which may be activated via the viewer's touch-screen, and the playing time. The screen- displayed information 214,216 remains fixed relative to the displayed text 218 as the viewer moves. Fig. 20 shows the view the viewer shows once the nearest video clip is 'snapped' to the screen, i.e. with the video clip filling the screen, ready to be played. As seen, all of the playback controls and playing time are displayed when the view is snapped. The user snaps the nearest interactive or dynamic object to the centre of the screen by pressing the viewer's snap button. Alternatively or additionally, an interactive object may snap to the screen automatically when activated, e.g. when played in the case of a video clip. In the example, status information and controls are superimposed on the video clip to maximize the video clip's use of the screen. The viewer 100 typically suppresses the display of the status information 216 and playback controls 214 once the clip is playing, either until the clip terminates or until the user initiates further interaction by touching the touch-screen 132. The playing time is preferably displayed in units of hours, minutes and seconds, and is preceded by a current chapter number if the clip has multiple chapters. The playback controls 214 include stop, play, pause, skip backwards and skip forwards. When the clip is stopped or paused, a play button is shown. When the clip is playing, a pause button is shown in place of the play button. The skip controls skip to the start/end of the current chapter, or, if already at the start/end, to the start of the previous/next chapter. If held, rather than pressed momentarily, the skip controls scan

backwards/forwards through the clip, i.e. they play the clip at a greater than normal rate backwards/forwards.

As an alternative to on-screen controls, the viewer may provide dedicated playback control buttons which control whichever dynamic object is current. It may also provide a dedicated display, such as a monochrome segment LCD, for the display of chapter (or track) information and playing time.

The viewer streams dynamic objects such as video clips from any number of servers via the current netpage base station. The viewer is optimized to only stream objects which are currently visible on the viewer's screen. When an object ceases to be displayed, it may be configured to automatically pause, or it may continue to 'play' on the server, without consuming communications bandwidth, so that when it is once again displayed its playback has progressed in time as expected by the user.

Figs. 21, 22 and 23 provide an example of the interaction of the viewer 100 with an audio clip. Fig. 21 shows a sample 'music library' page 220 containing multiple audio clip entries 224. The entries may be grouped under a title 222. Fig. 22 shows the view the viewer provides of a set of audio clip entries 224, which includes an indication of a 'current' audio clip entry with an associated play button 226 which may be activated via the viewer's touch-screen. The current entry is preferably simply the entry closest to the center of the screen and so changes as the viewer is moved, unless a clip is playing. If no entry is sufficiently close, then no entry is current. Fig. 23 shows the view the viewer provides once the nearest audio clip is snapped to the screen or selected, i.e. with clip-related information filling the screen. Note that, as illustrated in the example, a snapped view can be quite different from any view directly derivable from the page itself.

As described above, when the viewer is lifted from the page the portion of the page with which the viewer was last in contact remains displayed and interactive. It may also be advantageous for the user to be able to 'freeze' the current view so that the viewer no longer synchronizes the view with the underlying page. When the user snaps the nearest interactive or dynamic object to the screen the view is effectively frozen. When the user presses the snap button again, the viewer once again synchronizes the view with the underlying page. When there is no interactive or dynamic object to be snapped, the viewer may still interpret the snap as a freeze command, but may do no

more than rotate the current view so that it is oriented the right way up, i.e. so that the axes of the screen and of the displayed page are aligned. The snap button may therefore be used as a freeze button, but as an alternatively the viewer may provide a freeze button separate from the snap button.

5           The viewer may provide a mode wherein the axes of the screen and of the displayed page are always kept aligned even though the viewer is otherwise synchronizing the view with the underlying page, i.e. the viewer synchronizes the view according to the position and identity of the underlying page, but not according to the rotation of the underlying page relative to the viewer. This mode has the advantage that  
10 the displayed view always looks sensible to the user operating the viewer. It has the further advantage that rotation is never allowed to degrade the quality of the displayed image of the page. If rotation is never respected by the viewer, then the viewer is also freed from ever having to compute a rotated page image. As a compromise, the viewer may respect the nearest multiple of ninety degrees to its actual rotation relative to the  
15 page.

          Figs. 24 and 25 provide an example of the interaction of the viewer with 'secure' data requiring authorized access. Fig. 24 shows an example personal identification number (PIN) advice letter 230 from a bank. Both the account number 232 and PIN 234 are suppressed on the printed page, i.e. printed as a series of X's. Figure 14  
20 shows the view the viewer provides of the PIN advice letter. The view shows the actual account number 236 and PIN 238, on the basis that the netpage system has verified that the user of the viewer is the owner of the data. The advice letter is recorded on a netpage registration server as being owned by a particular user, i.e. by the user to whom the letter was originally addressed. The viewer is recorded as owned by the same user. The  
25 identity of the actual user is optionally verified with respect to the identity of the owner of the viewer by verifying the fingerprint of the actual viewer against the fingerprint of the owner. The fingerprint, or some other biometric, is recorded by the registration server for the owner. The viewer may incorporate a fingerprint sensor 189 for the purposes of fingerprint capture. Providing a biometric such as a fingerprint or signature to the viewer  
30 may place the viewer in a 'secure' mode wherein secure information is accessible for a period of time. An indicator, such as a lit LED, may indicate this mode to the user. Alternatively, secure access is only granted while the user's biometric is being sensed. In



the example, the actual account number and PIN is then only shown while the user's finger is in contact with the fingerprint sensor.

Figs. 26 and 27 provide an example of the interaction of the viewer with a fill-in form 240. The form has a number of fill-in fields 242. Fig. 26 shows an example form. Fig. 27 shows the view the viewer provides of the form. The stylus 244 can be used to fill in the fields of the form via the touch-screen. The example shows the form 240 being filled in by hand, pending handwriting recognition according to normal netpage mechanisms.

Netpage input, in the form of digital ink, is labeled to indicate how it was captured, i.e. through a netpage pen interacting with a printed netpage, or through a stylus interacting with the touch-sensitive screen of a viewer. The digital ink is also labeled with any change in the authorization state of the viewer, e.g. with respect to the presence of the user's finger on the viewer's fingerprint sensor. This allows the page server, when interpreting netpage input in relation to the corresponding page description, to ignore document elements not visible to the user when the input was captured.

Digital ink generated through a viewer is otherwise suitably transformed to look like it came from a netpage pen interacting with the underlying page, i.e. the digital ink is labeled with the page ID of the underlying page, and the coordinates of position samples in the digital ink are transformed from the coordinate system of the viewer into the coordinate system of the underlying page, according to the view transform current when the position sample was captured. As an alternative, the viewer may provide an insertion point specifiable via the stylus, an associated text cursor, and text entry via an on-screen keyboard or via character-wise character entry and recognition, in the manner of current personal digital assistants (PDAs).

The printer is most useful in filling out forms such as that displayed in Figures 26 and 27. The users uses the stylus 244 to "write" information onto the display, as shown in Figure 28. The display is updated to reflect the digital ink captured by the viewer.

Referring to Figure 33, the print assembly is controlled to print ink 260 in the fill-in fields of the form 240 to correspond to the digital ink captured by the touch screen. Thus at the end of the process an electronic version and a hard copy version of the

completed form exist. Printing of the ink 260 may occur as the user fills in each text box or it may occur after completion of the form. Printing after completion enables mistakes or alterations to be made before committing to paper but may require the user to move the viewer across the page to enable printing of all information. Printing as the user fills

5 in the form avoids the need to move the device to print information. However, unless an erasable marking system such as E-ink is used, all mistakes and alterations are printed to the page.

The printer assembly 200 may be used to physically transfers onto the underlying page any virtual markings made by the user via the viewer touch-screen.

10 Virtual strokes can be faithfully reproduced, including colors, textures, line widths, and even subtle brushing effects such as produced by striated brushes and airbrushes. The virtual marking mode of the stylus on the screen can be completely controlled in a position-dependent manner by the active application(s), i.e. as one expects in any graphical user interface.

15 In the limit case, a user interacts with Netpages exclusively via the Netpage printing viewer, eliminating the need for a Netpage Pen.

The printing viewer is designed to print when stationary with respect to the underlying page. Because the printhead 203 is screen-width, it can transfer the entire contents of the screen 102 onto the underlying page in a single pass. When not printing,

20 the printhead assembly 202 is parked in a recess to prevent accidental damage. To conserve power, the printhead assembly 202 can be parked at the top or bottom of the screen 102, and the printhead 203 can print when moving in either direction. To prevent user access to the cavity in which the printhead assembly moves, the assembly is integrated into a screen-width belt which also acts as the carriage transport. The belt

25 obscures the viewer's code sensor during printing, but contains pairs of matching holes which line up when the printhead is parked, providing the code sensor with a view of the surface. Two pairs of holes are provided, corresponding to the two parking positions.

Handwritten text can be transferred to the underlying page before or after it is recognized by the Netpage system and converted to computer text. If transferred after

30 conversion, the viewer can transfer the computer text to the underlying page in place of the handwritten text. Similarly, a signature can be transferred to the page before or after

it is used by the Netpage system to verify the identity of the user. If transferred after verification, the viewer can transfer a verification icon and/or a serial number in place of the signature.

The Netpage printing viewer can also be used to *paste* information onto a page, including images and text. The user may take a photo with a camera and paste it into an image field requiring the photo. The printing viewer links the photo to the image field and faithfully transfers the photo to the page, registered with the image field. If the viewer only partially overlaps the field, then only the portion of the field accessible to the viewer is printed with the photo. When the user moves the viewer across the field the viewer prints additional parts of the field. The viewer may prompt the user to move the viewer to cover un-printed portions of the field. Any un-printed portions of the image are recorded as pending output against the page instance maintained by the relevant Netpage page server. If a viewer comes into contact with the image field at a future time then any un-printed portions can be printed.

15 If the user pastes an image into a viewer-displayed image field when the viewer is not in contact with the page, then the entire image is recorded as pending output.

The printing viewer may incorporate a digital camera. Once the user takes a photo, it may “float” on the display as an icon until the user explicitly pastes it in an image field. The viewer may provide dedicated buttons for browsing, viewing, editing and deleting a collection of photos stored in the viewer. The viewer may also support removable storage, e.g. via a memory card socket, for storage of photos.

20 The user may also paste information which is known to the viewer or to the Netpage system, such as contact details, into a Netpage form which is not otherwise linked to the user.

25 The viewer may alternatively or additionally contain a mobile telephone transceiver for longer-range communication with a netpage server via a mobile telephone network. If the transceiver supports a third-generation ‘always-on’ packet-switched connection, then the viewer may download or stream page content at will. If the transceiver only supports a circuit-switched connection, then the viewer may choose to connect and download a full page description whenever it encounters a new page, provide local navigation of the page via the downloaded page description, and only make

further connections when dynamic content needs to be displayed or when hyperlinks are activated.

If the viewer incorporates a longer-range transceiver, then it may act as a netpage base station for wireless netpage pens and other netpage sensing devices.

- 5           When used to interrogate secure data, the viewer may incorporate a fingerprint sensor, such as the Vericom FPS200, to allow it to continuously monitor and verify the identity of the user. The processor typically interrogates the fingerprint sensor via a serial interface.

- 10           The viewer may incorporate several levels of power management. After a period of inactivity the viewer may inactivate the display. After a longer period of inactivity the processor may enter a power-conserving quiescent state. Power management may be coupled with the image sensor and/or the touch sensor, allowing wake-up on screen interaction or movement. The viewer may also incorporate an accelerometer for this purpose.

- 15           The viewer may be configured with software allowing it to function as a personal digital assistant (PDA). The components and functions of the viewer may also be incorporated into a mobile phone.

- 20           The viewer handles a variety of page content, including styled text, outline graphics, bitmapped images, audio, and video. While audio and video are by their nature dynamic (i.e. time-varying), text, graphics and images are normally static. They may, however, be part of a dynamic stream representing the output of an interactive application, executing remotely or within the viewer. A local application may be defined by a script object which is interpreted by the viewer, e.g. coded in Java or similar.

- 25           Page content falls into three categories: (1) static elements which appear on the printed page; (2) static elements which only appear through the viewer; and (3) dynamic elements which only appear through the viewer. The first category includes all the visual elements of the page. The second category includes, for example, elements associated with controls for dynamic content, e.g. playback controls for a video clip, and elements associated with secure information. The third category includes anything of a dynamic  
30           nature, e.g. a video clip. A dynamic element may have a static counterpart in the page

description so that it has a meaningful visual appearance on the printed page. A video clip, for example, may be represented by a rectangle of the appropriate size showing the title of the clip.

Document elements in the second and third categories have associated view  
5 filters 245 which restrict their appearance. The 'viewer view' 246 filter restricts the  
element to appearing through a viewer. The 'secure view' 247 filter restricts the element  
to appearing through an authorized viewer. The view filter class diagram is shown in Fig.  
31.

A digital ink stream is generated with a maximum data rate of about 5 Kbit/s.  
10 The viewer generates a view transform stream with a similar maximum data rate. The  
viewer therefore generates wireless communications traffic to the base station with a  
maximum data rate of about 10 Kbit/s, which is negligible.

To minimize wireless communications traffic from the base station to the  
viewer, it may be mandated that only one dynamic object can be active at a time. Even  
15 though more than one object may be visible through the viewer, the page server may  
deactivate all but one such object. It may, for example, only leave the dynamic object  
closest to the center of the viewer's display active. The user may be able to explicitly  
activate an alternative dynamic object by clicking on it with the stylus, or the user may  
be required to explicitly activate any dynamic object, thus implicitly deactivating any  
20 currently active object.

Where a dynamic object represents an application window, the page server  
typically relays to the application any changes to the viewer's view transform which  
relate to the application window. This allows the application to generate output when the  
window is visible, and to tailor the output to the actual overlap between the window and  
25 the viewer's view. The output from the application may be in the form of a video stream,  
or it may be in the form of a stream of graphics commands operating on text, graphics  
and images.

It is possible to display output from a remote application through the viewer,  
and capture stylus input through the viewer and route it to the remote application,  
30 without the application having to be explicitly designed for interaction with the viewer.  
Applications typically interact with user interface devices such as bitmapped displays,

keyboards and pointing devices in a device-independent manner by utilizing the services of a windowing system, and this allows the user interface devices to be remote from the applications without changing how the applications interact with them.

As an alternative to rendering the view on demand, the viewer may render the entire page into a memory buffer and then simply display a suitably transformed window into the buffer. However, since the rotation of relatively low-resolution text produces unacceptable text quality, the page must either be rendered at a higher resolution than the display resolution and appropriately lowpass filtered before display, or the display resolution must be higher than assumed so far.

As a further alternative, the viewer may rely on the page server or the base station to render the page and supply it to the viewer, typically in compressed form. In this case the viewer is still responsible for integrating dynamic streams with the static page view.

As yet another alternative, the viewer may rely on the page server or the base station to render the current view and supply it to the viewer, typically in compressed form. In this case the viewer need contain no support whatsoever for interpreting and rendering the variety of elements which may comprise a page description. Assuming a 320x240 RGB pixel display, a 10 Hz update rate, and 10:1 compression, this requires a data rate of about 1.8 Mbit/s, which is within the realms of practicality using currently-available personal-area, local-area and wide-area wireless networking technologies as discussed above.

Fig. 32 illustrates the interaction between the netpage viewer 100 and the netpage network. The viewer's time-varying view transform, as well as digital ink captured via the viewer, are transmitted (at A) to a netpage base station 290. The base station 290 relays (at B) the view transform and digital ink to the page server 291 which holds the electronic description of the physical page with which the viewer is interacting as identified by the page ID embedded in the tags of the page. The page server 291 interprets the view transform and digital ink with respect to the page, and initially responds (at C) with the page description. It subsequently transmits (at C) dynamic object updates and streaming dynamic content. The base station relays (at D) data from the page server to the viewer.

The page server may notify (at E) an application 292 that the viewer's view onto a window associated with the application has changed, and the application 292 may respond (at F) with commands instructing the viewer 100 to update parts of its current view. The page server 291 relays (at C) these commands to the base station 290, which  
5 relays (at D) the commands on to the viewer 100.

Whilst the display of the preferred embodiment is visual, a Braille viewer may be made according to the invention. A Braille viewer is analogous to the optical viewer. It displays in registered fashion and via a tactile Braille display the text of a netpage. It also displays text labels corresponding to graphics and images, where available in the  
10 page description. Because Braille characters are typically rendered at larger sizes than visually-recognized characters, the Braille viewer typically presents a zoomed view of the underlying page. This means that as the viewer is moved over the page, the display moves correspondingly faster.

In other embodiments the viewer can be transparent when it is not in contact  
15 with a page, so that while it is being placed on a page, the page is seen through the viewer. This can be implemented using a LCD shutter which is reflective when opaque, positioned behind a transmissive color display. However, the netpage viewer design is simplified if the viewer is always opaque, and only ever virtually transparent.

Whilst the invention has been described with reference to the netpage system  
20 which uses invisible tags, the invention is not limited to the netpage system or the use of invisible tags. If desired, the invention may utilize tags or codes which are visible to the average unaided human eye, such as bar codes. The tags need not merely encode an identity which is then used to look up the relevant files. The tags may encode instructions at a higher level. For example a tag may encode an instruction of "play  
25 chapter 99". If invisible tags are used they need not be limited to the tags disclosed in relation to the netpage system. Other tagging systems are available and any suitable tagging system may be used. The invention is not limited to the use of inks which absorb certain wavelengths or fluoresce certain wavelengths. Magnetic inks, surface modification, including apertures, modification of the structure of the substrate itself all  
30 fall within the scope of the invention. The systems and methods to link the viewer of the present invention and the source of the document data are not limited to netpage systems.

A viewer may be linked by a cable to a single computer, rather than a network of computers.

The present invention has been described with reference to a preferred embodiment and number of specific alternative embodiments. However, it will be appreciated by those skilled in the relevant fields that a number of other embodiments, differing from those specifically described, will also fall within the spirit and scope of the present invention. Accordingly, it will be understood that the invention is not intended to be limited to the specific embodiments described in the present specification, including documents incorporated by cross-reference as appropriate. The scope of the invention is only limited by the attached claims.



## CLAIMS

1. A viewing device including:
  - at least one sensor for sensing coded data on or in a substrate and for generating
  - 5 first data;
  - a transmitter for transmitting, to a computer system, said first data or second data at least partially based on the first data;
  - a receiver for receiving, from the computer system, at least display data associated with an identity derived from the first data;
  - 10 at least one display device for outputting visual information based at least partially on said display data, and
  - a printer mechanism for printing on the substrate.
2. A viewing device according to claim 1 wherein the visual output corresponds to a human discernable interface on the substrate.
- 15 3. A viewing device according to claim 1 further including a user interface and control means operable to cause the printer mechanism to print markings on the substrate based at least partially on user input and/or the display data.
4. A viewing device according to claim 3 wherein the user interface includes a touch sensitive overlay.
- 20 5. A viewing device according to claim 5 wherein the printer mechanism prints markings on the substrate as a user interacts with the touch screen overlay.
6. A viewing device according to claim 5 wherein the printer mechanism prints markings on the substrate after a user has completed interaction with the touch sensitive overlay.
- 25 7. A viewing device according to claim 6 wherein user input to the touch screen overlay is uploaded to the computer system and the computer system downloads data based on the uploaded data for printing on the substrate.

## ABSTRACT

A viewer (100) is provided for displaying and allowing interaction with interactive information and application interfaces. The viewer includes at least one code  
5 sensor (112) for sensing coded data (202) disposed on a surface (200). The viewer transmits data derived from the sensed data to a computer system and receives, in response, data for display on a color display (102). The visual content of the display may be synchronized with the visual content of the underlying coded surface. The viewer also includes a printer mechanism (200) for transferring to the underlying surface input  
10 captured via a touch-sensitive overlay (132) on the display (102).

(Figure 7)

FIG. 7 is a block diagram of a viewer (100) according to one embodiment of the present invention. The viewer (100) includes a code sensor (112) for sensing coded data (202) disposed on a surface (200). The viewer (100) transmits data derived from the sensed data to a computer system (104) and receives, in response, data for display on a color display (102). The viewer (100) also includes a printer mechanism (200) for transferring to the underlying surface input captured via a touch-sensitive overlay (132) on the display (102).




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8

FIG. 9 is a perspective view of the device 100 in a closed position, showing the housing 110, the display 120, the camera 130, the microphone 140, the speaker 150, the sensor 160, the antenna 170, the battery 180, and the user interface 190.




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15



FIG. 16




FIG. 17






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25

**Application Form**

Name

Address

Telephone

242

240

FIG. 26

**Application Form**

Name

Address

Telephone

242

240

244

100

FIG. 27

**Application Form**

Name

Address

Telephone

242

240

FIG. 28




FIG. 29




FIG. 30






FIG. 31




FIG. 32

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION</b> (37 CFR 1.63)	<b>Attorney Docket Number</b>	<b>NPS018US</b>
	<b>First Named Inventor</b>	<b>PAUL LAPSTUN</b>
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	/
	<b>Filing Date</b>	
	<b>Group Art Unit</b>	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	<b>OR</b>	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
	<b>Examiner Name</b>	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**VIEWER WITH CODE SENSOR AND PRINTER**

the specification of which (Title of the Invention)

☒ is attached hereto  
OR  
☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
PQ4392	Australia	12-01-1999	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.**DECLARATION — Utility or Design Patent Application**

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number  OR  
☐ Registered practitioner(s) name/registration number listed below

Place Customer  
Number Bar Code  
Label here

Name	Registration Number	Name	Registration Number


☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number or Bar Code Label **24011** OR ☒ Correspondence address below

Name	Kia Silverbrook				
Address	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	ZIP	2041
Country	Australia	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])		Family Name or Surname	
PAUL		LAPSTUN	
Inventor's Signature			Date
			Nov. 22, 2000
Residence: City	Rodd Point	State	NSW
		Country	Australia
Post Office Address	13 Duke Avenue		
Post Office Address			
City	Rodd Point	State	NSW
		ZIP	2046
		Country	Australia

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐Approved for use through 9/30/98 OMB 0651-0032  
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

**DECLARATION****ADDITIONAL INVENTOR(S)**  
**Supplemental Sheet**  
Page 1 of 1**Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

**KIA****SILVERBROOK**Inventor's  
Signature

Date

**Nov. 22,  
2000**

Residence: City

**Balmain**

State

**NSW**

Country

**Australia**

Citizenship

**Australian**

Post Office Address

**393 Darling Street**

Post Office Address

City

**Balmain**

State

**NSW**

ZIP

**2041**

Country

**Australia****Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

**TOBIN ALLEN****KING**Inventor's  
Signature

Date

**Nov. 22,  
2000**

Residence: City

**Cremorne**

State

**NSW**

Country

**Australia**

Citizenship

**Australian**

Post Office Address

**Unit 2, 125 Cremorne Road**

Post Office Address

City

**Cremorne**

State

**NSW**

ZIP

**2090**

Country

**Australia****Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Inventor's  
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Burden Hour Statement. This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.